



# Shell Radiator Cleaner

## Automotive Radiator Cleaner and Flush Fluid

**Shell Radiator Cleaner is an engine coolant system flushing fluid which is suitable for use in all automotive and heavy duty petrol, diesel and gas engines.**

### Applications

Shell Radiator Cleaner can be used in all petrol, diesel and gas engine cooling systems in.

The product is suitable for use in both light duty applications (such as automobiles, motorbikes and taxis); and also in heavy duty applications (such as long haul and short haul trucks and vans, and construction and heavy duty equipment).

It can also be used in the cooling systems of stationery generator engines and leisure marine engines.

### Performance Features and Benefits

- Will remove all rust and scale
- Compatible with all coolant types
- Suitable for light duty and heavy duty engine types

### Product Use

Prepare a Flushing solution by adding 10% of Shell Radiator Cleaner fluid to 90% water, and mix thoroughly

Drain the old coolant charge, and fill the radiator coolant system with the prepared flushing solution.

Run the engine on light idle for 10-15 minutes, then fully drain the engine coolant flush.

For best results, repeat the process.

Fill the engine system with water and run the engine on light idle for 10 -15 minutes. Fully drain the water.

Replace with finished good quality ready-to-use coolant (such as Shell coolant products), and ensure all radiator fittings are tightly secured, including the radiator cap.

The system is now fully flushed and ready for use.

### Specifications and Approvals

Suitable for use in all engine coolant systems in petrol, diesel and gas engines

### Health & Safety

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Recochem representative.

### Protect the Environment

Take used coolant products to an authorised collection point. Do not discharge into drains, soil or water.

### Shelf Life

When stored undercover, away from moisture and direct sunlight, this product should be suitable for use for up to three years after the date of manufacture.





### Typical Physical and Chemical Characteristics

Radiator Cleaner	Units	Typical
Appearance		Brown Liquid
pH		11.5
Boiling Point	Deg C	100

These characteristics are typical of current production. Whilst future production will conform to Recochem's specification, variations in these characteristics may occur.

