



# Shell Speed Wax

## Spray and Wipe on Wax solution

Shell Speed Wax is a spray and wipe on solution which gives an immediate smooth, high gloss, protective finish on automotive surfaces, and produces a powerful water beading effect.

### Applications

Shell Speed Wax can be applied simply on cleaned automotive painted surfaces to produce a highly finished glossy protective coating, which produces a powerful water-beading effect.

The produce can be applied by simply spraying onto the surface and then wiping off for a smooth finish.

For best results, apply on clean surfaces after washing with Shell Car Shampoo.

### Performance Features and Benefits

- Removes water spots and gives a smooth glossy finish and a great car shine
- Won't strip sealants or waxes
- Ideal for regular paint care between washes
- Can be applied to all exterior paint finishes and chrome parts.

### Health & Safety

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Recochem representative.

### Protect the Environment

Take used products to an authorised collection point. Do not discharge into drains, soil or water.

### Shelf Life

This product is to be stored undercover, in dry conditions at ambient temperature below 30°C, and away from direct sunlight and possible moisture ingress.

When stored under such conditions, with the cap and packaging remained sealed, then the shelf life of the product is 5 years. Once opened and unsealed, the product should be fully consumed as soon as possible.

### Typical Physical and Chemical Characteristics

Speed Wax	Units	Typical
Appearance		White Opaque Liquid
Density (SG) at 20C	kg/m <sup>3</sup>	1.00 approx
pH		6-8

These characteristics are typical of current production. Whilst future production will conform to Recochem's specification, variations in these characteristics may occur.

