



Recochem Inc.

Your Partner in Formulating Solutions
Votre partenaire branché sur les solutions

Shell Wax Paste

Shell Wax Paste is a premium Crystal Wax formulation designed to provide superior protection to automotive paintwork with a mirror-like glossy finish.

Application

The product is used as protectant for automotive paint and to give it a mirror-like glossy shine

Directions of Use

Wash and dry vehicle thoroughly before use
Gently dab the supplied applicator into the pot whilst turning.

Apply to clean and dry paintwork in a circular motion, making sure to leave behind an even and thin layer.

Allow wax to dry for approximately 5-10 minutes, then buff to a high gloss finish using a clean microfiber cloth.

Do not wax the vehicle under direct sunlight

Performance Features and Benefits

- **Excellent Protection**

Helps protect paintwork from scuffing, oxidation, acid rain and other contaminants.

- Provides a mirror-like glossy finish with excellent depth, clarity and detail whilst repelling water.

- **Long Lasting**

A single application can last as long as 3 months

Specifications and Approvals

The product is suitable for use on all standard automotive paintwork

Health & Safety

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Recochem representative.

Protect the Environment

In the event of disposal, take any unused product to an authorised collection point. Do not discharge into drains, soil or water.

Shelf Life

This product is to be stored undercover, in dry conditions at ambient temperature below 30°C, and away from direct sunlight and possible moisture ingress.

When stored under such conditions, with the cap and packaging remained sealed, then the shelf life of the product is 3 years. Once opened and unsealed, the product should be fully consumed as soon as possible.





Typical Physical and Chemical Characteristics

Wax Paste	Units	Typical
Appearance		Wax Paste
Colour		Yellow

These characteristics are typical of current production. Whilst future production will conform to Recochem's specification, variations in these characteristics may occur.

